Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration Essentially similar to Non-Mandatory Approved O.S.H.A. Form OMB No. 1218-0072

IDENTITY

745 SYN-O-GEN EP 75W90 GEAR LUBRICANT

SECTION I

Primrose Oil Company, Inc. 11444 Denton Drive P.O. Box 29665 Dallas, Texas 75229 Emergency Only Telephone No. 800/633-8253 Telephone Number for Information: 972-241-1100 Date Prepared: February 1, 2009

SECTION II - Hazardous Ingredients Identity/Information

None

SECTION III - Physical/Chemical Characteristics

(Butyl Acetate = 1)

Solubility in Water: Insoluble

Appearance and Odor:. Red colored liquid with mild petroleum odor.

SECTION IV - Fire and Explosion Hazard Data

Flash Point (Method Used): 235°C (COC), min Flammable Limits: undetermined LEL: UEL: N/A. N/A.

Extinguishing Media: CO2, dry chemical, foam, or water fog.

Special Fire Fighting Procedures: Wear self-contained breathing apparatus for fires in confined spaces.

Unusual Fire and Explosion Hazards: N/A.

SECTION V - Reactivity Data

Stability: Unstable: Conditions to Avoid: Contact with strong oxidizers

Stable: XX

Incompatibility (Materials to Avoid): Liquid chlorine, oxygen

Hazardous Decomposition or Byproducts: carbon monoxide and asphyxiants

Hazardous May Occur: Conditions to Avoid: Contact with strong oxidizers

Polymerization: Will Not Occur: XX

SECTION VI - Health Hazard Data

Route(s) of Entry: Inhalation? yes Skin?: yes Ingestion? yes

Health Hazards (Acute and Chronic): Threshold limit Value: 5 mg/m³ as a mist. LD50 in rats is 5 gm/kg.

Carcinogenicity: N/A.

Signs and Symptoms of Exposure: May cause skin irritation with prolonged or repeated contact.

Medical Conditions Generally Aggravated by Exposure: Not established.

Emergency and First Aid Procedures: For ingestion, DO NOT induce vomiting. Obtain medical assistance. For small amounts that accidentally enter mouth or eye, rinse with water until gone.

SECTION VII - Precautions for Safe Handling and Use

Steps to Be Taken In Case Material Is Released or Spilled: Absorb with inert material.

Waste Disposal Method: Follow federal, state, and local regulations.

Precautions to Be Taken in Handling and Storing: Keep away from heat and open flame. NFPA Class IIIB Storage.

Other Precautions: Wash thoroughly after handling.

SECTION VIII - Control Measures

Respiratory Protection (Specify Type): None needed under normal conditions with adequate ventilation.

Ventilation: Local Exhaust: Special:

Mechanical (General): Other: As needed to comply with TLV

goggles if splashing anticipated.

Other Protective Clothing or Equipment: Not normally required.

Work/Hygienic Practices: Avoid skin and eye contact. Wash thoroughly after handling. Launder soiled clothes.

745 MSDS