

## **745 Syn-O-Gen EP 75W90 Gear Lubricant**

**Description:** 745 Syn-O-Gen EP 75W90 is 100% pure synthetic GL-5 gear lubricant for heavy-duty extreme pressure performance in all types of gear drives and specifically for rear axles.

**Composition:** 745 Syn-O-Gen is compounded using a synthetic basestock which has a high viscosity index and exceptionally low pour point. This lubricant contains extreme pressure additives, as well as rust, oxidation and corrosion inhibitors to protect gears and bearings operated under a wide variety of load conditions. The high and low temperature performance of this product greatly exceeds that of conventional SAE 80W-90 and SAE 90 hypoid gear lubricants.

**Performance Characteristics:** 745 Syn-O-Gen outperforms conventional gear lubricants to promote longer gear life and better operating economy. Some of the major advantages are:

**Increased gear life** - 745 Syn-O-Gen's extreme pressure (EP) performance results in longer gear life by providing extremely high film strength and superior low-temperature performance. It also has anti-rust and anti-corrosion properties to further promote extended gear and bearing life. This lubricant exhibits excellent demulsibility and shear stability.

**Better operating performance** - As a result of the superior lubricating properties of Syn-O-Gen EP, improved fuel mileage is increased. When used in manual transmissions, sub-zero shifting is much easier.

**Extended drain, all-season lubrication** - With extremely low channel points and high viscosity indices, 745 Syn-O-Gen provides excellent performance over a broad temperature range. Further, since Syn-O-Gen EP resists oxidation, it will last significantly longer than conventional gear oils.

**Reduced maintenance and down-time** - All of the foregoing advantages of Syn-O-Gen EP translates directly into reduced maintenance and less down-time.

**Uses:** 745 Syn-O-Gen meets and exceeds the following performance requirements:

API Classification GL-5+/MT-1	Harnischfeger (P&H) 474
Dana Axle	Mack Truck GO-G/S
Eaton Axle	MIL-L-2105D
General Electric D50E9C	Rockwell International 0-76-E



**PRIMROSE OIL COMPANY, INC.**

11444 Denton Drive / P.O. Box 29665 / Dallas, Texas 75229-0665/ 972.241.1100/ 800.275.2772/ Fax: 972.241.4188

**Applications:**

745 Syn-O-Gen EP is recommended for applications where heat and wear present major problems. These applications include manual transmissions where EP type lubricants are recommended, differentials including limited slip, and transfer cases for heavy equipment, trucks, tractors and industrial gear drives. Automobiles light-duty trucks and farm machinery are other potential uses of Syn-O-Gen EP Lubricants.

**Specifications:**

<b>Property</b>	<b>Product Data</b>	<b>Test Method</b>
SAE Grade	75W-90	J306-b
AGMA Grade	4 EP	ASTM D-2422
Viscosity, cSt		ASTM D-445
100°C	18.0	
40°C	132	
Viscosity, SUS		ASTM D-2161
210°F	90	
100°F	612	
Viscosity, cP		ASTM D-2983
-18°C (0°F)	7,125	
-40°C (-40°F)	140,000	
Viscosity Index	152	ASTM D-2270
Channel Point, °C (°F)	-51.1 (<-60)	FTMS 3456
Pour Point, °C (0°F)	<-45.6 (<-50)	ASTM D-97
Flash Point, °C (°F)	207.2 (405)	ASTM D-92
Foam Test		ASTM D-892
Sequence I	pass	
Sequence II	pass	
Sequence III	pass	
API Gravity, 15.6/15.6°C	24.3	ASTM D-287
Density, g/l (lbs./gal.), 15.6°C	905.9 (7.56)	
Copper strip corrosion		ASTM D-130
3 hrs. at 100°C	pass	
3 hrs. at 121°C	pass	
Thermal heat test, 148.9°C	pass	Rckw. 076E
Timken OK Load	50	
Demulsibility	pass	Wheeling Steel Test